



# 1/2" Square Drive Universal Wrenches METRIC

## 6 Point and 12 Point Hex, Standard and Tension Type



Part # 6 Point	Part # 12 Point	Hex Opening	Overall Length (A)	Socket Length (B)	Socket Diameter (C)	Nose End Diameter (D)	Clearance Depth (E)
3852	3852-D	12	76	23.8	22.2	17.5	10.3
3853	3853-D	12	102	23.8	22.2	17.5	10.3
3854	3854-D	12	152	23.8	22.2	17.5	10.3
3855	3855-D	12	229	23.8	22.2	17.5	10.3
3856	3856-D	12	305	23.8	22.2	17.5	10.3
3857	3857-D	13	76	25.5	22.2	17.5	11.9
3858	3858-D	13	102	25.4	22.2	17.5	11.9
3859	3859-D	13	152	25.4	22.2	17.5	11.9
3860	3860-D	13	229	25.4	22.2	17.5	11.9
3861	3861-D	13	305	25.4	22.2	17.5	11.9
3862	3862-D	14	102	27.0	22.2	19.1	13.5
3863	3863-D	14	152	27.0	22.2	19.1	13.5
3864	3864-D	14	229	27.0	22.2	19.1	13.5
3865	3865-D	14	305	27.0	22.2	19.1	13.5
3866	3866-D	15	76	28.6	25.4	19.8	14.3
3867	3867-D	15	102	28.6	25.4	19.8	14.3
3868	3868-D	15	152	28.6	25.4	19.8	14.3
3869	3869-D	15	229	28.6	25.4	19.8	14.3
3870	3870-D	15	305	28.6	25.4	19.8	14.3
3871	3871-D	16	76	30.2	25.4	21.4	15.9
3872	3872-D	16	102	30.2	25.4	21.4	15.9
3873	3873-D	16	152	30.2	25.4	21.4	15.9
3874	3874-D	16	229	30.2	25.4	21.4	15.9
3875	3875-D	16	305	30.2	25.4	21.4	15.9
3876	3876-D	17	76	31.8	25.4	25.4	17.5
3877	3877-D	17	102	31.8	25.4	25.4	17.5
3878	3878-D	17	152	31.8	25.4	25.4	17.5
3879	3879-D	17	229	31.8	25.4	25.4	17.5
3880	3880-D	18	76	31.8	25.4	25.4	17.5
3881	3881-D	18	102	31.8	25.4	25.4	17.5
3882	3882-D	18	152	31.8	25.4	25.4	17.5
3883	3883-D	18	229	31.8	25.4	25.4	17.5
3884	3884-D	18	305	31.8	25.4	25.4	17.5
3885	3885-D	19	76	34.9	31.8	26.2	16.3
3886	3886-D	19	102	34.9	31.8	26.2	16.3
3887	3887-D	19	152	34.9	31.8	26.2	16.3
3888	3888-D	19	229	34.9	31.8	26.2	16.3
3889	3889-D	19	305	34.9	31.8	26.2	16.3

**Sockets can be configured with the following options:**

**S = Standard (Floppy)**

**T = Tension**

**FM = Fixed Magnetic**

PHONE (248) 549-1968 FAX (248) 549-1960

WWW.LANCETOOLS.COM