

# 3/8" Square Drive Universal Wrenches

## 6 Point and 12 Point Hex, Standard and Tension Type Extensions



Part # 6 Point	Part # 12 Point	Hex Opening	Overall Length (A)	Socket Length (B)	Socket Diameter (C)	Nose End Diameter (D)	Clearance Depth (E)
2270	2270-D	3/8	3.00	.812	.625	.531	.437
2271	2271-D	3/8	4.00	.812	.625	.531	.437
2272	2272-D	3/8	6.00	.812	.625	.531	.437
2273	2273-D	3/8	9.00	.812	.625	.531	.437
2274	2274-D	7/16	3.00	.875	.625	.625	.500
2275	2275-D	7/16	4.00	.875	.625	.625	.500
2276	2276-D	7/16	6.00	.875	.625	.625	.500
2277	2277-D	7/16	9.00	.875	.625	.625	.500
2278	2278-D	7/16	12.0	.875	.625	.625	.500
2279	2279-D	7/16	3.00	.937	.750	.593	.500
2280	2280-D	7/16	4.00	.937	.750	.593	.500
2281	2281-D	7/16	6.00	.937	.750	.593	.500
2282	2282-D	1/2	3.00	.875	.687	.687	.500
2283	2283-D	1/2	4.00	.875	.687	.687	.500
2284	2284-D	1/2	6.00	.875	.687	.687	.500
2285	2285-D	1/2	9.00	.875	.687	.687	.500
2286	2286-D	1/2	12.0	.875	.687	.687	.500
2287	2287-D	1/2	3.00	1.00	.750	.750	.562
2288	2288-D	1/2	4.00	1.00	.750	.750	.562
2289	2289-D	1/2	6.00	1.00	.750	.750	.562
2290	2290-D	1/2	9.00	1.00	.750	.750	.562
2291	2291-D	1/2	12.0	1.00	.750	.750	.562
2292	2292-D	9/16	3.00	1.00	.812	.812	.562
2293	2293-D	9/16	4.00	1.00	.812	.812	.562
2294	2294-D	9/16	6.00	1.00	.812	.812	.562
2295	2295-D	9/16	9.00	1.00	.812	.812	.562
2296	2296-D	9/16	12.0	1.00	.812	.812	.562
2297	2297-D	5/8	3.00	1.12	.875	.875	.593
2298	2298-D	5/8	6.00	1.12	.875	.875	.593
2299	2299-D	5/8	12.0	1.12	.875	.875	.593

**Sockets can be configured with the following options:**

**S = Standard (Floppy)**

**T = Tension**

**FM = Fixed Magnetic**