

3/8" Square Drive Universal Wrenches METRIC

6 Point and 12 Point Hex, Standard and Tension Type



Part # 6 Point	Part # 12 Point	Hex Opening	Shank Length (A)	Socket Length (B)	Socket Diameter (C)	Nose End Diameter (D)	Clearance Depth (E)
2560	2560-D	10	76	20.6	19.1	15.1	9.5
2561	2561-D	10	102	20.6	19.1	15.1	9.5
2562	2562-D	10	152	20.6	19.1	15.1	9.5
2563	2563-D	10	229	20.6	19.1	15.1	9.5
2564	2564-D	10	305	20.6	19.1	15.1	9.5
2565	2565-D	11	76	23.8	22.2	15.9	10.3
2566	2566-D	11	152	23.8	22.2	15.9	10.3
2567	2567-D	11	229	23.8	22.2	15.9	10.3
2568	2568-D	11	305	23.8	22.2	15.9	10.3
2569	2569-D	12	76	23.8	22.2	17.5	10.3
2570	2570-D	12	102	23.8	22.2	17.5	10.3
2571	2571-D	12	152	23.8	22.2	17.5	10.3
2572	2572-D	12	229	23.8	22.2	17.5	10.3
2573	2573-D	12	305	23.8	22.2	17.5	10.3
2574	2574-D	13	76	25.4	22.2	17.5	11.9
2575	2575-D	13	102	25.4	22.2	17.5	11.9
2576	2576-D	13	152	25.4	22.2	17.5	11.9
2577	2577-D	13	229	25.4	22.2	17.5	11.9
2578	2577-D	13	305	25.4	22.2	17.5	11.9
2579	2579-D	14	76	27.0	22.2	19.1	13.5
2580	2580-D	14	102	27.0	22.2	19.1	13.5
2581	2581-D	14	152	27.0	22.2	19.1	13.5
2582	2582-D	14	229	27.0	22.2	19.1	13.5
2583	2583-D	14	305	27.0	22.2	19.1	13.5
2584	2584-D	15	76	28.6	25.4	19.8	14.3
2585	2585-D	15	102	28.6	25.4	19.8	14.3
2586	2586-D	15	152	28.6	25.4	19.8	14.3
2587	2587-D	15	229	28.6	25.4	19.8	14.3
2588	2588-D	15	305	28.6	25.4	19.8	14.3

Sockets can be configured with the following options:

S = Standard (Floppy)

T = Tension

FM = Fixed Magnetic